



### Klemmlängen für HV-Garnituren (EN 14399-4)

Die Klemmlänge  $\Sigma_t$  in mm umfasst auch die beiden HV-Scheiben. Der Wert  $l_k$  zeigt die reine Klemmlänge nach Abzug der zwei Scheiben.

Länge (mm)	M12		M16		M20		M24		M27		M30	
	$\Sigma_t$	$l_k$	$\Sigma_t$	$l_k$	$\Sigma_t$	$l_k$	$\Sigma_t$	$l_k$	$\Sigma_t$	$l_k$	$\Sigma_t$	$l_k$
30	11-16	6-10										
35	16-21	11-15										
40	21-26	16-20	17-22	10-14								
45	26-31	21-23	22-27	15-19	18-23	10-14						
50	31-36	24-28	27-32	20-24	23-28	15-19						
55	36-41	29-33	32-37	25-29	28-33	20-24						
60	41-46	34-38	37-42	30-34	33-38	25-29	29-34	22-26				
65	46-51	39-43	42-47	35-39	38-43	30-34	34-39	27-31				
70	51-56	44-48	47-52	40-44	43-48	35-39	39-44	32-36	36-41	28-32		
75	56-61	49-53	52-57	45-47	48-53	40-44	44-49	37-41	41-46	33-37	39-44	29-33
80	61-66	54-58	57-62	48-52	53-58	45-49	49-54	42-46	46-51	38-42	44-49	34-38
85	66-71	59-63	62-67	53-57	58-63	50-54	54-59	47-51	51-56	43-47	49-51	39-43
90	71-76	64-68	67-72	58-62	63-68	55-57	59-64	52-53	56-61	48-52	54-59	44-48
95	76-81	69-73	72-77	63-67	68-73	58-62	64-69	54-58	61-66	53-57	59-64	49-53
100	81-86	74-78	77-82	68-72	73-78	63-67	69-74	59-63	66-71	58-60	64-69	54-56
105			82-87	73-77	78-83	68-72	74-79	64-68	71-76	61-65	69-74	57-61
110			87-92	78-82	83-88	73-77	79-84	69-73	76-81	66-70	74-79	62-66
115			92-97	83-87	88-93	78-82	84-89	74-78	81-86	71-75	79-84	67-71
120			97-102	88-92	93-98	83-87	89-94	79-83	86-91	76-80	84-89	72-76
125			102-107	93-97	98-103	88-92	94-99	84-88	91-96	81-85	89-94	77-81
130			107-112	98-102	103-108	93-97	99-104	89-93	96-101	86-90	94-99	82-86
140					113-118	103-107	109-114	99-103	106-111	96-100	104-109	92-96
150					123-128	113-117	119-124	109-113	116-121	106-110	114-119	102-106
160							129-134	119-123	126-131	116-120	124-129	112-116
Stärke von 2 Scheiben (mm)	6		8		8		8		10		10	